



- 3.0 Mp resolution
- Built-in microphone and speaker
- MicroSD card support
- Pan and Tilt control
- SMD IR LED
- Wireless connect
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan mac
- Human tracking

Your manual is here:

<https://www.doc.myershome.eu/wifirobot>



Myers software:

<https://my.partizanccloud.com/get-our-mobile-app>



IP Camera		
Model		Myers Home WiFi Robot
Version		-
SKU		5932
Image Sensor		
Sensor		1/2.7" CMOS sensor
Pixel Size, μm		3.0x3.0
Resolution, pixels@fps	Mainstream (max)*	PAL: 2304*1296@12FPS NTSC: 2304*1296@12FPS
	Substream (max)*	PAL: 800*448@12FPS NTSC: 800*448@12FPS
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0,01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		
Codec		H.265X
		Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		3,6
Iris, F		1,2
Angle of View, °	Horizontal	74
	Vertical	46
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control	Pan, °	355
	Tilt, °	90
IR LED		
Distance, m		≤10
Number of LEDs, pcs.		4PCS IR LED+4PCS White LED
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		-
Wireless LAN Standart / Frequency, Ghz		802.11(b/g/n) / 2.4
Supported encryption type	AES	+
	TKIP	+
	AES+TKIP	-
Network functions		Partizan MAC protocol/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPAddress:port/user=admin&password=admin&channel=1&stream=0.sdp?
Snapshot capture link		http://IPAddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin
Control port		34567
Configuration software		Myers (Setup Tool), Myers Device Manager
Monitoring program		Myers
Mobile software (support)		Myers
Protocol integration		Myers SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	115
	Housing	Ø70x115
	Bracket	-
Weight, g		360

Common		
Power Supply	DC5V, A	1,1
	PoE Class/W	-
Alarm	Inputs	-
	Outputs	-
Audio, G.711A	Built-in microphone	+
	Built-in speaker	+
Memory card		MicroSD (≤128Gb)
Accessories		Power supply 5V/1.6A with cable 3m
Housing material, plastic/metal		+/-
Bracket material, plastic/metal		+/-
IP rating		44
IK rating		-
Operating temperature, °C		+10 - +50
Warranty, years		3