



- Wi-Fi IP camera
- 3Mp resolution
- IP67 rating
- IR + White LED + Smart Detection, 24/7 Full Colour
- 3-Axis mounting
- ONVIF 2.4 protocol support

Your manual is here:

www.doc.myershome.eu/wifikit



Myers software:

<https://my.partizancloud.com/get-our-mobile-app>



IP Camera		
Model		Myers Wifi KIT Bullet
Version		3MP
SKU		6016
Image Sensor		
Sensor		1/2.7" Full HD CMOS Sensor
Pixel Size, μm		2.8x2.8
Resolution, pixels@fps	Mainstream (max)*	PAL: 2048 x 1536@12fps NTSC: 2048 x 1536@12fps
	Substream (max)*	PAL: 640x360@12fps NTSC: 640x360@12fps
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0,01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AEC, AGS, AWB, ABF, BLC, OSD, PrivacyMasks
Smart functions		Human detection
Codec profile	H.265	Baseline / Main / High
Exposure mode, s	Auto	1/25-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the		
Lens		
Focal length, mm		3,6
Iris, F		1,4
Angle of View, °	Horizontal	77
	Vertical	61
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-
IR LED		
Distance, m		≤25
Number of LEDs, pcs.		2 double IR and White led
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Wireless LAN	Standard	802.11(b/g/n)
	Frequency, Ghz	2.4, 5db antenna
	Max. wireless	<100
Network functions		Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP/HTTP/SMTP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Username		admin
Password		
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPAddress:port/user=admin&password=&channel=1&stream=0.sdp?
Snapshot capture link		http://IPAddress/webcapture.jpg?command=snap&channel=1&user=admin&password=
Control port		34567
Configuration software		Myers (Setup Tool), Myers Device Manager
Monitoring program		Myers
Mobile software (support)		Myers
Protocol integration		Myers SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	185
	Housing	60x70x110
	Bracket	70
Weight, g		350

Common		
Power Supply	DC12V, A	0,5
	PoE Class/W	-
Audio		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		67
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3