



- 5.0 Mp resolution
- High sensitivity
- Built-in microphone
- MicroSD card support
- Smart functions support
- IP66 rating
- IR LED
- 3-Axis mounting
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Remote access to the device with Partizan MAC

Your manual is here:

www.doc.myershome.eu/wifibullet



Myers software:

<https://my.partizanccloud.com/get-our-mobile-app>



IP Camera		
Model		Myers Outdoor
Version		WiFi Bullet
SKU		5933
Image Sensor		
Sensor		1/2.7"SC335E Low illumination CMOS sensor
Pixel Size, μm		2.9x2.9
Resolution, pixels@fps	Mainstream (max)*	PAL: 2592*1944@12fps,
	Substream (max)*	PAL:640*360@12fps,
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0.001Lux @F1.2
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AES, AGC, AWB, BLC, OSD, PrivacyMasks
Smart functions in camera		Human detection
Smart functions when using together with Cloud-series NVR		Human detection / Human Perimeter Intrusion Detection / Human Line Crossing Detection
Codec profile	H.265	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		3,6
Iris, F		1,4
Angle of View, °	Horizontal	87-90
	Vertical	47-50
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-/-
IR LED		
Distance, m		≤20
Number of LEDs, pcs.		4 Warm White IR
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Wireless LAN Standard / Frequency, Ghz		802.11b/g/n 2.4G External double Wifi Antenna
Supported encryption type	AES	+
	TKIP	+
	AES+TKIP	-
Network functions		Partizan MAC protocol/ DDNS/IPFilter/ E-mail/NTP/UPNP/RTSP/HTTP/HTTPS/TCP/IPV4
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Username		admin
Password		admin
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPAddress:port/user=admin&password=admin&channel=1&stream=0.sdp?
Snapshot capture link		http://IPAddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin
Control port		34567
Configuration software		Myers (Setup Tool), Myers Device Manager, Web interface
Monitoring program		Myers
Mobile software (support)		Myers
Protocol integration		Myers SDK, ONVIF 2.4+

Dimensions		
Size, mm	Total length	175
	Housing	175x70x65
	Bracket	Ø70
Weight, g		650
Common		
Power	DC12V, A	0,6
Supply	PoE Class/W	0/5
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	+
	Inputs	-
	Built-in speaker	+
Memory card		MicroSD (≤128Gb)
Accessories		Power supply 12V/1A cable 3m
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		66
IK rating		-
Operating temperature, °C		-20 - +55
Warranty, years		3